

全自動下壓式起動 Full-auto push to start shut off



型號 Model No.	無載轉速 No load speed r.p.m	重量 Weight g	全長 Length mm	直徑 Diameter mm	嘈音 Noise dBA	氣喉內徑 Hose inner diameter mm	耗氣量 Air consumption m ³ /min	扭力範圍 Torque range kgf.cm	精度 Accuracy %	適用螺絲 Applicable screw (mm)	
										機牙 Machine screw	自攻 Tapping screw
AD-20P	1000	530	180	31	70	5.0	0.2	1-8	±3	M1.7~M3.3	M1.3~M2.7
AD-30P	1800	530	180	31	74	5.0	0.28	3-17	±3	M2.2~M4.2	M1.7~M3.2
AD-40P	1000	530	180	31	74	5.0	0.28	5-30	±3	M2.8~M5.0	M2.2~M4.0

批咀 Bit : 6.35mm

半自動手按式起動 Semi-auto lever start shut off



型號 Model No.	無載轉速 No load speed r.p.m	重量 Weight g	全長 Length mm	直徑 Diameter mm	適用螺絲 Applicable screw mm	氣喉內徑 Hose inner diameter mm	耗氣量 Air consumption m ³ /min	最大扭力 Maximum Torque Nm	嘈音 Noise dBA
SA-5	1600	650	140	35	3~5	5.0	0.28	5.0	72
SA-6	1700	840	195	43	5~6	8.0	0.55	7.0	77

批咀 Bit : 6.35mm